



EQUIPMENT PRODUCT INFORMATION
BL190 TAPED BAG LOADER

DESCRIPTION

The CRYOVAC® brand BL190 delivers fast, consistent manual loading for operations focused on throughput, hygiene, and product integrity. Built for efficiency, it reduces labor, simplifies changeovers, and minimizes contamination risk, all while maintaining a clean, professional package appearance. Designed to work seamlessly with CRYOVAC® brand shrink bags, the BL190 helps preserve freshness and flavor, making it a powerful tool for boosting productivity and protecting your brand.



KEY BENEFITS

OPERATIONAL EFFICIENCY	<ul style="list-style-type: none">Reduce labor costs by streamlining the manual bag-loading processMinimize downtime with quick and easy changeovers and reloadingHandles multiple bag formats and sizes including both side- and end-sealed taped bagsProvides layout flexibility with both right- and left-hand configurations
PRODUCT INTEGRITY	<ul style="list-style-type: none">Enhances food safety and lowers risk of contamination by reducing human contact during loadingHygienic stainless steel design that facilitates simplified cleaning and maintenancePreserves product quality and freshness when paired with CRYOVAC® brand shrink bags
BRAND EXPERIENCE	<ul style="list-style-type: none">Delivers consistent product quality that supports your brand's reputation for freshness and flavor

TECHNICAL DATA

MACHINE DIMENSIONS

Length	28" (711 mm)
Width	30.5" (775 mm)
Height	50.5" (1283 mm)

WEIGHT

Weight	260 lbs (118 kg)
Construction	Stainless Steel

MATERIAL DIMENSIONS

Bag Width	4"-16" wide (101 mm- 406 mm) up to 24" (609 mm) long
Bag Type	Barrier E and Super L Bags

WORKING SPEED

Speed	Up to 40 ppm
-------	--------------

UTILITIES

Air	60 psig, 5 CFM, 3/8" supply line
Electrical	1-phase, 115 VAC, 60 Hz, 1 AMP

LINE LAYOUT EXAMPLE

