

Autobag®

BRAND AUTOMATED SYSTEMS

Pre-opened bags

A wide range of film types for any bag packaging application



We manufacture a wide variety of pre-opened poly bags and our UK-based extrusion, printing and conversion capabilities ensure high quality packaging.

We offer many film types for any packaging application:

STANDARD FILM – LINEAR, LOW-DENSITY POLYTHENE

- Superior strength and durability
- Ideal for any industrial and retail application
- Fully recyclable
- Material colour: a wide range of plain and custom printing

HIGH CLARITY FILM – POLYPROPYLENE

- High bag transparency, high strength and odour transfer resistant
- Ideal for foods, crafts and retail applications
- Material colour: a wide range of plain and custom printing

MAILBAG FILM – LINEAR, LOW-DENSITY POLYTHENE

- Black on the inside, white on the outside for privacy
- Designed for fulfilment applications
- Fully recyclable
- Optional matt finish available

ANTISTATIC FILM – POLYTHENE WITH ANTISTATIC ADDITIVE

- Dissipates static electricity
- Ideal for electrical and electronic components
- Fully recyclable
- Material colour: clear, pink or white

RECYCLED FILM – UP TO 95% PRE-CONSUMER RECYCLED CONTENT

- Environmentally responsible and durable
- Ideal for any industrial and retail application
- Fully recyclable
- Material colour: grey or green shades for end-user awareness

OTHER SPECIFIC FILM TYPES:

- Translucent UV inhibiting film
- Electrostatic discharge shielding film
- Anticorrosion film





Customise your bags for your specific packaging application:

CUSTOM PRINTING AVAILABLE ON EVERY FILM TYPE

- All our bags can be printed in up to 8-colours, including Pantone®-matched and metallic inks
- Our in-house graphics department works with you for precise print registration, colour matching and uniformity
- Our capabilities include line, screen and process printing on one or both sides of the bag

SPECIAL FEATURES AVAILABLE ON EVERY FILM TYPE

- Air relief hole
- Easy open perforation
- Hanger hole
- Compartments
- Reclosable adhesive tape

SPECIFICATIONS

Compliance	ISO 9001, ISO 14001, BCR
Flexographic printing	Yes
In-line printing	Yes
Bag thickness	35, 50, 75 and 100 µm*
Bag widths	55-550 mm
Bag lengths	70-900 mm

*EXCEPT:

- High clarity film: 50 and 65 µm
- Antistatic film: 50, 75 and 100 µm
- Recycled film 50 and 75 µm
- Electrostatic discharge shielding film: 80 µm

Features, Options and Technical Specifications subject to change.

SUSTAINABILITY

As a maker of flexible packaging products, we recognise the need for greater awareness and involvement in creating a more sustainable planet – from the point of manufacture to the point of disposal.

For over a decade, we have been producing environmentally responsible products for our customers. We introduced GeoTech®, a line of pre-consumer reprocessed films that forever changed the packaging industry. We have introduced innovative, lighter gauge films that reduce the amount of material required without compromising packaging performance. In addition, our machinery technology continues to evolve with new, state-of-the-art components and engineering designed to reduce energy consumption.

